



The X299 platform supports the newest Skylake-X and Kaby Lake-X processors. EVGA X299 motherboards further refine high-performance with multiple options for all the latest SSD options with support for U.2, M.2 and PCI-E drives and is Intel® Optane™ Memory Ready – a revolutionary higher-density memory interface, based on 3D XPoint Technology, delivers a new generation of SSDs designed to obliterate loading times for gamers. However, the X299 platform also supports all the features you've come to expect from EVGA, including up to 64GBs of Quad-Channel DDR4 memory up to 4000MHz+ for Skylake-X, and 4133MHz+ for Kaby Lake-X (OC), Gigabit-NIC support, USB 3.0 and USB 3.1 Type-A and Type-C support, an updated UEFI\BIOS GUI, PWM fan control and a variety of SATA options to fit everyone's needs. The X299 Micro ATX is built with a 8-layer PCB, featuring a CPU socket with 150% higher Gold content powered by an Advanced 12-phase Digital VRM (10 Phase VCore, 2 Phase Memory PWM), providing industry-leading stability for all your applications.

Furthermore, this board is designed not ONLY for overclockers, but also for gamers with NVIDIA® 2-Way SLI Support without the need for PLX chips, blazing-fast networking from an Intel i219 and a 802.11AC Dual Band WiFi, M.2 Key-M, U.2, 6 SATA 3/6g and much more! Big power in a small form factor, size is NOT a sacrifice for the EVGA X299 Micro ATX!

DESIGN DETAILS

Supported CPUs -

Intel® 7th Generation Socket 2066 Extreme Series Processors

Socket Type - Intel® Socket 2066

PCH - Intel® X299

DIMM QTY - 4 DIMM Quad-Channel

Memory Type - DDR4 4000MHz+ (SKX), 4133MHz+ (KBX) Memory Capacity - 64GB

SATA 6.0Gb/s Ports/Controller - 6 / Intel® X299 PCH RAID Support - RAID 0, 1, 5, and 10

USB 2.0 Ports/Controller -

4 Ports (2 from internal header) / Intel® X299 PCH USB 3.0 Ports/Controller - 6 (2 from internal header) / Intel® X299 PCH USB 3.1 Ports/Controller - 1x Type-A, 1x Type-C

Network Speed - 10/100/1000

Network Ports/Controller -

802.11AC Dual Band + Intel i219 Gigabit NIC

Audio - 7.1 Channel HD Audio

Audio Controller - HD 7.1 Channel Audio + Optical

PCI-E Slot Arrangement - 3x16 (bottom x4)
PCI-E x16 Mechanical Slots - 3

M.2 / 1x Key-M - 1x 80mm (Up to 32Gbps) **M.2 / 1x Key-E**

BIOS Type - Full UEFI with mouse/keyboard control **Software -** EVGA E-LEET X Tuning Utility

Fan Headers - 6 4-Pin (2 PWM, 4 DC/PWM)

KEY SPECS

- Supports Intel® Core™ 7th Generation Processor Family for 2066 socket
- 150% Increased Gold Content
- Intel® X299 Chipset
- Enthusiast Layout Supporting 2-Way SLI®
- 4 DIMM Quad-Channel up to 64GB 4000MHz+ Skylake-X, and 2 DIMM Dual-Channel up to 32GB 4133MHz+ Kaby Lake-X
- PCI Express® 3.0 Ready
- 4 USB 2.0 Ports (2 internal headers)
- 8 USB 3.0 Ports (6 rear panel, 2 from 1 internal header)
- 2 USB 3.1 Ports (1x Type-A, 1x Type-C)
- Intel® Optane Support
- 6 SATA
- 1 M.2 Key-M 80mm up to 32Gbps
- •1M.2 Key-E 32mm
- •1U.2 Port
- 802.11AC Dual Band + Intel i219 Gigabit NIC (10/100/1000)
- mATX Form Factor

DIMENSIONS

- Width: 9.6in 243.8mm
- Length: 9.6in 243.8mm
- Form Factor: mATX Form Factor

ACCESSORIES

- EVGA Driver Installation Disc with EVGA E-LEET
- Rear Case I/O Panel
- Rear Case I/O Cover
- 2 SATA 6G Data Cables
- M.2 Key-E 802.11AC Dual Band Wifi and vertical Adapter
- Enthusiast Stickers
- Case Badge
- Manual








































PRODUCT WARRANTY

www.evga.com/warranty.











The second secon

