











- · A-Style : Home Cloud
- Supports 4th Gen Intel® Core™ i7 / i5 / i3 / Xeon® / Pentium® / Celeron® in LGA1150 Package
- · All Solid Capacitor design, Digi Power
- Supports Dual Channel DDR3 2800+(OC)
- 1 x PCle 3.0 x16, 3 x PCle 2.0 x1
- Multi-VGA Output Options : DVI-D, D-Sub, HDMI
- · Intel Gigabit LAN
- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec)
- 6 x SATA3, 6 x USB 3.0, 6 x USB 2.0
- Supports A-Tuning, XFast 555, Easy Driver Installer, FAN-Tastic Tuning, USB Key





















Detail Specification

Platform	- ATX Form Factor - All Solid Capacitor design
A-Style	- Home Cloud
СРИ	- Supports 4 th Generation Intel [®] Core [™] i7 / i5 / i3 / Xeon [®] / Pentium [®] / Celeron [®] in LGA1150 Package - Digi Power Design - 4 Power Phase Design - Supports Intel [®] Turbo Boost 2.0 Technology - Supports Intel [®] K-Series unlocked CPU - Supports ASRock BCLK Full-range Overclocking
Chipset	- Intel® Z87
Memory	- Dual Channel DDR3 memory technology - 4 x DDR3 DIMM slots - Supports DDR3 2800+(OC)/2400(OC)/2133(OC)/1866(OC)/1600/1333/1066 non-ECC, un-buffered memory - Max. capacity of system memory: 32GB - Supports Intel® Extreme Memory Profile (XMP) 1.3 / 1.2
Expansion Slot	- 1 x PCI Express 3.0 x16 slot (PCIE2: x16 mode) - 3 x PCI Express 2.0 x1 slots - 2 x PCI slots
Graphics	* Intel® HD Graphics Built-in Visuals and the VGA outputs can be supported only with processors which are GPU integrated. - Supports Intel® HD Graphics Built-in Visuals: Intel® Quick Sync Video with AVC, MVC (S3D) and MPEG-2 Full HW Encode1, Intel® InTru™ 3D, Intel® Clear Video HD Technology, Intel® Insider™, Intel® HD Graphics 4400/4600 - Pixel Shader 5.0, DirectX 11.1 - Max, shared memory 1792MB - Three VGA Output options: D-Sub, DVI-D and HDMI - Supports Triple Monitors - Supports HDMI Technology with max. resolution up to 1920x1200 @ 60Hz - Supports DVI-D with max. resolution up to 1920x1200 @ 60Hz - Supports DVI-D with max. resolution up to 1920x1200 @ 60Hz - Supports Auto Lip Sync., Deep Color (12bpc), xyYCC and HBR (High Bit Rate Audio) with HDMI (Compliant HDMI monitor is required) - Supports HDCP function with DVI-D and HDMI ports
Audio	- 7.1 CH HD Audio with Content Protection (Realtek ALC892 Audio Codec) - Premium Blu-ray audio support
LAN	- Gigabit LAN 10/100/1000 Mb/s - Giga PHY Intel® I217V - Supports Intel® Remote Wake Technology - Supports Wake-On-LAN - Supports Energy Efficient Ethernet 802.3az - Supports PXE
Rear Panel I/O	I/O Panel -1 x PS/2 Mouse/Keyboard Port -1 x D-Sub Port -1 x DVI-D Port -1 x INDMI Port -2 x USB 2.0 Ports -4 x USB 3.0 Ports -1 x RJ-45 LAN Ports with LED (ACT/LINK LED and SPEED LED) - HD Audio Jack: Side Speaker / Rear Speaker / Central / Bass / Line in / Front Speaker / Microphone

Storage	- 6 x SATA3 6.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 5, RAID 10, Intel Rapid Storage Technology 12 and Intel Smart Response Technology), NCQ, AHCI and Hot Plug
Connector	- 1 x IR header - 1 x COM port header - 1 x Power LED header - 2 x CPU Fan connectors (1 x 4-pin, 1 x 3-pin) - 2 x Chassis Fan connectors (2 x 4-pin) - 1 x Power Fan connector (3-pin) - 1 x 24 pin ATX power connector - 1 x 8 pin 12V power connector - 1 x Front panel audio connector - 1 x SPDIF Out connector - 2 x USB 2.0 headers (support 4 USB 2.0 ports) - 1 x USB 3.0 header (supports 2 USB 3.0 ports)
BIOS Feature	- 64Mb AMI UEFI Legal BIOS with Multilingual GUI support - ACPI 1.1 Compliance Wake Up Events - SMBIOS 2.3.1 Support - CPU, DRAM, PCH 1.05V Voltage Multi-adjustment
Support CD	- Drivers, Utilities, AntiVirus Software (Trial Version), CyberLink MediaEspresso 6.5 Trial Google Chrome Browser and Toolbar, Start8, MeshCentral, Splashtop Streamer
Unique Feature	- ASRock A-Tuning - ASRock Instant Flash - ASRock XFast USB - ASRock XFast USB - ASRock XFast LAN - ASRock XFast RAM - ASRock Crashless BIOS - ASRock OMG (Online Management Guard) - ASRock UEFI System Browser - ASRock UEFI System Browser - ASRock UEFI System Browser - ASRock Dehumidifier Function - ASRock Dehumidifier Function - ASRock Easy RAID Installer - ASRock Easy Driver Installer - ASRock Hoteractive UEFI - ASRock Fast Boot - ASRock On/Off Play Technology - ASRock On/Off Play Technology - ASRock USB Key - ASRock FAN-Tastic Tuning - Hybrid Booster: - CPU Frequency Stepless Control - ASRock U-COP - Boot Failure Guard (B.F.G.)
Hardware Monitor	- CPU/Chassis Temperature Sensing - CPU/Chassis/Power Fan Tachometer - CPU/Chassis Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature) - CPU/Chassis Fan Multi-Speed Control - Voltage Monitoring: +12V, +5V, +3.3V, CPU Vcore
OS	- Microsoft® Windows® 8 / 8 64-bit / 7 / 7 64-bit compliant
Certifications	- FCC, CE, WHQL - ErP/EuP Ready (ErP/EuP ready power supply is required)
Accessories	- Quick Installation Guide, Support CD, I/O Shield - 2 x SATA Data Cables









All the capacitors on this board are built with 100% all solid capacitors. With these solid caps, ASRock motherboards are allowed to perform more stably and ensure longer lifetime.





By adopting digital Pulse-width modulation (PWM), the ASRock motherboard can provide CPU Vcore voltage more efficiently and smoothly.



A-Tuning is ASRock's multi purpose software suite with a new interface, more new features and improved utilities, including XFast RAM, OC Tweaker and a whole lot more.



This motherboard supports Triple-Monitor. You may choose up to three display interfaces to connect monitors and use them simultaneously.



ASRock's unique XFast 555 technology (XFast RAM, XFast LAN and XFast USB) allows users to experience 5 times performance boost in terms of system performance, LAN speed and USB transfer speed.



Configure different fan speeds for respective temperatures using the graph. The fans will automatically shift to the next speed level when the assigned temperature is met.



For users that don't have an optical disk drive to install the drivers from our support CD, Easy Driver Installer is a handy tool in the UEFI that installs the LAN driver to your system via an USB storage device, then downloads and installs the other required drivers automatically.



Just plug in the USB Key and let your computer log in to windows automatically without having to type your username and password!



Contact ASRock Tech Service by sending a support request form from the UEFI setup utility if you are having trouble with your PC.



With ASRock's exclusive Fast Boot technology, it takes less than 1.5 seconds* to logon to Windows 8 from a cold boot. No more waiting! The speedy boot will completely change your user experience and behavior. *The boot time may vary with a different configuration.





ASRock "Restart to UEFI" technology is designed for those requiring frequent UEFI access. It allows users to easily enter the UEFI SETUP automatically when turning on the PC next time.



The UEFI system browser allows you to easily check your current system configuration in UEFI setup.



ASRock OMG technology allows you to establish an internet curfew or restrict internet access at specified times. Administrators are able to schedule the starting and ending hours of internet access granted to other users.



Users may prevent motherboard damages due to dampness by enabling "Dehumidifier Function". When enabling Dehumidifier Function, the computer will power on automatically to dehumidify the system after entering S4/S5 state.