

Data Sheet

Barracuda ES.2

High-capacity, business-critical
enterprise drives

**1 TB, 750 GB, 500 GB and 250 GB • 7200 RPM •
SATA 3Gb/s, SATA 1.5Gb/s and SAS 3Gb/s**

Key Advantages

- 1-TB drive delivers 33 percent more capacity than the Barracuda ES drive.
- The industry's highest-reliability 7200-RPM drive, designed for 24x7 operation
- Best-in-class rotational vibration tolerance ensures unrivalled performance in high spindle-density applications, and multi-drive firmware maximizes system availability.
- Seagate® PowerTrim™ technology dynamically optimizes power consumption by improving GB/watt by 55 percent and reducing overall drive power consumption by 20 percent over prior-generation Barracuda ES drives.

Best-Fit Applications

- Storage-hungry business applications
- Network attached storage (NAS)
- Maximum-capacity servers
- Rich media content storage—audio, video, image
- Reference and compliance data storage
- Enterprise backup and restore—D2D, virtual tape
- Collaboration—email, messaging
- Infrastructure—Web, print, file



Barracuda ES.2

High-capacity business-critical enterprise drives



Seagate Makes the Best Even Better with a 5-Year Limited Warranty

- 1-TB Seagate® Barracuda® ES.2 drive provides 33 percent more capacity than its predecessor.
- With a choice of either SATA or SAS interfaces, the Barracuda ES.2 drive utilizes perpendicular recording technology to deliver the industry's highest-capacity 4-platter drive.
- The best 7200-RPM reliability for 24x7 business-critical applications from a trusted source, backed by a 5-year limited warranty
- Multi-drive firmware features and best-in-class rotational vibration (RV) tolerance maximizes system availability and performance in multi-drive systems. Seagate proprietary Workload Management technology helps systems keep drives cool.

Seagate Global Customer Support

- Get presales and technical support at support.seagate.com.
- Visit our knowledge base for answers to common support questions.
- Find documentation for current and legacy drives.
- Utilize our online troubleshooting and diagnostic tools.
- Download DiscWizard™ to help migrate data from an older drive.
- Seagate also offers multi-lingual phone, email and chat support.
- Seagate Design Service Centers (DSC) help companies transform innovative ideas into viable products.

www.seagate.com

1-800-SEAGATE (1-800-732-4283)

Specifications	1 TB ¹	750 GB ¹	500 GB ¹	250 GB ¹
Model Number	ST31000340NS ST31000640SS	ST3750330NS ST3750630SS	ST3500320NS ST3500620SS	ST3250310NS
Interface	SATA 3Gb/s, 1.5Gb/s SAS 3Gb/s	SATA 3Gb/s, 1.5Gb/s SAS 3Gb/s	SATA 3Gb/s, 1.5Gb/s SAS 3Gb/s	SATA 3Gb/s, 1.5Gb/s
External Transfer Rate (Gb/s)	3.0	3.0	3.0	3.0
Performance				
Transfer Rate				
Maximum Internal (Mb/s)	1287	1287	1287	1287
Maximum Sustained (MB/s)	105	105	105	105
Cache, Multisegmented (MB)				
SATA	32	32	32	32
SAS	16	16	16	—
Average Latency (msec)	4.16	4.16	4.16	4.16
Spindle Speed (RPM)	7200	7200	7200	7200
Seek Time				
Average Read/Write (msec)	8.5/9.5	8.5/9.5	8.5/9.5	8.5/9.5
Track-to-Track Read/Write (msec)	0.8/1.0	0.8/1.0	0.8/1.0	0.8/1.0
Configuration/Organization				
Bytes per Sector				
SATA	512	512	512	512
SAS	512, 520, 524, 528	512, 520, 524, 528	512, 520, 524, 528	—
Reliability/Data Integrity				
Mean Time Between Failures (MTBF, hours)	1.2 million	1.2 million	1.2 million	1.2 million
Reliability Rating at Full 24x7 Operation (AFR)	0.73%	0.73%	0.73%	0.73%
Nonrecoverable Read Errors per Bits Read	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15	1 sector per 10E15
Error Control/Correction (ECC)	10 bit	10 bit	10 bit	10 bit
Interface Ports				
SATA	Single	Single	Single	Single
SAS	Dual	Dual	Dual	—
Limited Warranty (years)	5	5	5	5
Power Management				
Typical (W)				
SATA	11.6	11.6	10.6	10.6
SAS	13.0	13.0	13.0	—
Idle Average (W)				
SATA	8.0	8.0	8.0	8.0
SAS	10.2	10.2	10.2	—
Environmental				
Temperature, Operating (°C)	5 to 55	5 to 55	5 to 55	5 to 55
Temperature, Nonoperating (°C)	–40 to 70	–40 to 70	–40 to 70	–40 to 70
Shock, Operating: 2 ms (Gs)	63	63	63	63
Shock, Nonoperating: 2 ms (Gs)	300	300	300	300
Acoustics Idle (bels—sound power)	2.7	2.7	2.5	2.5
Rotational Vibration @ 1500 Hz max (Rad/sec ²)	12.5	12.5	12.5	12.5
Physical				
Height (in/mm)	1.02/26.11	1.02/26.11	1.02/26.11	1.02/26.11
Width (in/mm)	4/101.6	4/101.6	4/101.6	4/101.6
Depth (in/mm)	5.78/146.99	5.78/146.99	5.78/146.99	5.78/146.99
Weight (lb/kg)	≥1.168/≥0.530	≥1.168/≥0.530	≥1.168/≥0.530	≥1.168/≥0.530

¹ One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to hard drive capacity.

AMERICAS Seagate Technology LLC 920 Disc Drive, Scotts Valley, California 95066, United States, 831-438-6550
ASIA/PACIFIC Seagate Technology International Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888
EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 130-136, rue de Silly, 92773, Boulogne-Billancourt Cedex, France 33 1-4186 10 00

Copyright © 2007 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Barracuda, DiscWizard and PowerTrim are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. One gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting. Seagate reserves the right to change, without notice, product offerings or specifications. DS1627.2-0708US, August 2007