



EF 70-200mm f/2.8L IS II USM
Specification Sheet

Optical Features/Specifications

Angle of view (horizontal, vertical, diagonal)	29° - 10°, 19°30' - 7°, 34° - 12°
Lens construction (elements/groups)	23/19
No. of diaphragm blades	8
Minimum aperture	32
Closest focusing distance (m)	1.2
Maximum magnification (x)	0.21 (at 200mm)
Distance information	Provided
Image stabilizer	4-stops
AF actuator	Ring USM ¹

Physical Specifications

Dust/moisture resistance ²	Yes
Filter diameter (mm)	77
Max. diameter x length (mm)	88.8 x 199
Weight (g)	1490g

Accessories

Lens cap	E-77U
Lens hood	ET-87
Lens case/pouch	LZ1326
Maximum number of Hood III compatible with Gelatin Filter Holder III	Not compatible
Maximum number of Hood IV compatible with Gelatin Filter Holder IV	1
Magnification with Extension Tube EF12 II	0.28 - 0.06
Magnification with Extension Tube EF25 II	0.36 - 0.14
Extender compatibility	Compatible

All data is based on Canon standard testing methods except where indicated.

Subject to change without notice.

[1] Full time manual focus.

[2] Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.