

**PRODUCTS**

MasterView - 2 Port KVM Switch: CS-912



The Master View CS-912 KVM Switch is a control unit that allows access to two PC systems from a single console (keyboard, mouse, and monitor). There are two convenient methods to access the connected PCs: with the push button Selection Switch located on the unit's side panel; and entering Hot Key combinations from the keyboard.

Setup is fast and easy; plugging cables into their appropriate ports is all that is entailed. There is no software to configure, no installation routines, and no incompatibility problems. Since the Master View CS-912 intercepts keyboard input directly, it works on any hardware platform and with all operating systems.

There is no better way to save time and money than with a Master View CS-912 installation. By allowing a single console to manage both of the attached PCs, the Master View CS-912 eliminates the expense of purchasing a separate keyboard, monitor, and mouse for each PC. Additionally, it saves all the extra space they would take up, and eliminates the inconvenience and wasted effort involved in constantly having to move from one PC to the other.

Features:

1. Supports Microsoft IntelliMouse, Logitech MouseMan, FirstMouse, IBM Scrollpoint Mouse....
2. Keyboard and Mouse Emulation for Error Free PC Booting
3. Caps Lock, Num Lock, and Scroll Lock States are Saved and Restored When Switching
4. Supports 1920 x 1440 Resolution
5. Easy to Install - No Software Required - Standard Cables to Connect to the PCs Is All It Takes
6. Easy to Operate - PC Selection via Pushbutton Switch or Hot Keys - Auto Scan Function to Monitor PC Operation

7. Compatible With All Operating Platforms
8. LED Display For Easy Status Monitoring
9. Saves Time, Space, Power and Equipment Costs
10. Nonpowered
11. Supports DDC2B (Display Data Channel)

Specifications:

Function		Specification
PC Connections		2
PC Selection		Pushbutton Switch Hot Keys
Connectors	Keyboard	1 x 6 pin mini-DIN Female - Console 2 x 6 pin mini-DIN Female - CPU Ports
	Mouse	1 x 6 pin mini-DIN Female - Console 2 x 6 pin mini-DIN Female - CPU Ports
	Video	1 x 15 pin HDB Female - Console 2 x 15 pin HDB Male - CPU Ports
LEDs		2 Selected Port Indicators
Emulation	Keyboard	PS/2
	Mouse	PS/2
VGA Resolution		1920 x 1440 (max.)
Scan Interval		5 Seconds
Power Consumption		DC 9V 80mA (max.)
Operating Temperature		5 ~ 40° C
Storage Temperature		-20 ~ 60° C
Humidity		0 ~ 80% RH, Noncondensing
Housing		Plastic
Weight		140 g
Dimensions (L x W x H)		100 x 85 x 27 mm