

**PRODUCTS**

MasterView - 4 Port KVM Switch: CS-914



The Master View CS-914 KVM Switch is a control unit that allows access to four PC systems from a single console (keyboard, mouse, and monitor). There are two convenient methods to access the connected PCs: with a push button Selection Switch, and by entering Hot Key combinations from the keyboard.

Setup is fast and easy; plugging cables into their appropriate ports is all that is entailed. There is no software to configure, no installation routines, and no incompatibility problems. Since the Master View CS-914 intercepts keyboard input directly, it works on any hardware platform and with all operating systems.

There is no better way to save time and money than with a Master View CS-914 installation. By allowing a single console to manage both of the attached PCs, the Master View CS-914 eliminates the expense of purchasing a separate keyboard, monitor, and mouse for each PC. Additionally, it saves all the extra space they would take up, and eliminates the inconvenience and wasted effort involved in constantly having to move from one PC to the other.

Features:

1. Supports Microsoft IntelliMouse and the Scrolling Wheel on Most Wheel Mice
2. Keyboard and Mouse Emulation for Error Free PC Booting
3. Easy to Install - No Software Required - Standard Cables to Connect to the PCs Is All It Takes
4. Easy to Operate - PC Selection via Pushbutton Switch or Hot Keys - Auto Scan Function to Monitor PC Operation
5. LED Display For Easy Status Monitoring
6. Supports 1920 x 1440 Resolution; DDC2B

7. Hot Pluggable
8. Caps Lock, Num Lock, and Scroll Lock States are Saved and Restored When Switching
9. Compatible With All Operating Platforms
10. Saves Time, Space, Power and Equipment Costs
11. Nonpowered

Specifications:

Function		Specification
PC Connections		4
PC Selection		Pushbutton Switch Hot Keys
Connectors	Keyboard	1 x 6 pin mini-DIN Female - Console 4 x 6 pin mini-DIN Female - CPU Ports
	Mouse	1 x 6 pin mini-DIN Female - Console 4 x 6 pin mini-DIN Female - CPU Ports
	Video	1 x 15 pin HDB Female - Console 4 x 15 pin HDB Male - CPU Ports
LEDs		4 Selected Port Indicators
Emulation	Keyboard	PC AT / PS/2
	Mouse	PS/2
VGA Resolution		1920 x 1440 (max.)
Scan Interval		3 Seconds
Power Consumption		DC 9V 80mA (max.)
Operating Temperature		5 ~ 40° C
Storage Temperature		-20 ~ 60° C
Humidity		0 ~ 80% RH, Noncondensing
Housing		Plastic
Weight		250 g
Dimensions (L x W x H)		170 x 87 x 28.5 mm