

Specification of HS5790D3

Rev 1.0

Wireless USB PC to TV Kit

HS5790D3	
Model Name	HS5790D3
Technology	UWB(Ultra Wide Band : 3.1GHz ~ 10.6GHz)
Data rate	Up to 480Mbps
Working distance	Up to 10m(5m for smooth video) at LOS
Connectors on RX device	HDMI V1.3 D-sub VGA SPDIF Out Audio out(3.5mm) USB2.0 port DC-IN
TX dongle Interface	USB 2.0
Max. display resolution	Display Resolution up to 2048x1152(QWXGA) Video Streaming 1080p 30fps, latency less than 20ms
Supported Video Display Modes	Mirror Desktop, Extended Desktop, Primary Display
LED light	Power, RF Signal strength(3 level color)
Power Supply	Output : DC 5V/1.5A
Power consumption	0.5A @5V (Without USB IO port devices)

Dimension(mm)	170(W) x 85(D) x 26(H)
Weight(g)	440g(full package)
Antenna	PCB pattern antenna for TX dongle, Dipole antenna for RX device
Operating condition	5 to 35 °C(41 to 95 °F) / 20 to 80 % relative humidity
Non-operating condition	-20 to 65°C(-4 to 149 °F)/10 to 90% relative humidity
Package contents	Wireless RX device, Wireless TX dongle, AC power adaptor, installation CD including electronic manual
Environment	RoHS Compliant
Operating System Support	Microsoft Windows XP with SP2 Microsoft Vista 32/64 Microsoft Windows 7 Microsoft Windows 8.0 Microsoft Windows 8.1
Warranty	One-year limited warranty

Product picture.

