

RS 130

Wireless Surround
Sound Experience

The RS 130 wireless RF headphone system with switchable surround sound is an ideal choice for both hi-fi and TV use. The lightweight RS 130 lets you enjoy freedom of movement up to approx. 150 metres from the audio source. In addition, the transmitter features a convenient metal stand for storing and recharging the headphones.



SRS 
Headphone

- Open, circumaural wireless stereo RF headphone system
- For hi-fi and TV use
- Switchable surround sound mode
- Intelligent auto-tuning due to automatic transmitter search tuning with memory function
- Optimum signal reception due to self-learning automatic level control
- Very lightweight headphones, extremely comfortable to wear
- Stylish design
- Range – up to 150 m (RS 130 – 864 MHz) or up to 100 m (RS 130 – 926 MHz)
- Easy recharging: simply hang the headphones onto the charging cradle
- Rechargeable NiMH batteries included
- Optional wall mounting (transmitter) possible
- Acoustic signals provide feedback on many functions
- Operating time: approx. 22 hours
- 2-year warranty



Specifications



Model	RS 130 (864 MHz) RS 130 (864 MHz-UK) RS 130 (926 MHz)				
Headphones	HDR 130 (864 MHz) HDR 130 (926 MHz)				
EAN No.	40 12418 09923 7	40 12418 09924 4	—	40 12418 09932 9	—
UPC No.	—	—	6 15104 09925 8	—	6 15104 09933 3
Cat. No.	009923	009924	009925	009932	009933
Design	Headphones: black with silver-coloured mesh; Transmitter: grey-black with charging cradle (chrome-plated)				
Frequency response	18–21,000 Hz				
Transducer principle	dynamic, open				
Max. SPL at 1 kHz	104 dB				
THD	< 0.5%				
Ear coupling	circumaural				
Weight	approx. 275 g				
Power supply	2.4 V – 3 V via 2 AAA size NiMH batteries (LR 03)				
Operating time of headphone batteries	approx. 22 h				
Transmitter	TR 130				
Modulation	FM stereo				
Range	up to 150 m (RS 130 – 864 MHz), up to 100 m (RS 130 – 926 MHz)				
Signal-to-noise ratio	typ. > 68 dBA				
Carrier frequencies	863.3; 864.0; 864.7 MHz or variant with 926.1; 926.8; 927.5 MHz				
Audio connector	3.5 mm stereo jack plug with adaptor to 1/4" (6.3 mm); RCA connector (926 MHz)				
Packaging					
Design	recloseable cardboard box with hanging eyelet				
Packaging dimensions in mm (W x H x D)	225 x 315 x 140 mm				
Master carton dimensions in mm (W x H x D)	480 x 360 x 720 mm				
Units per master carton	10				
Languages	German, English, French, Italian, Spanish, Dutch				