



HyperX Cloud Headset

Game without pain.

Let your opponents take the blows while you game without pain. HyperX® Cloud cradles your head in a super-soft padded headband, memory foam ear cushions and leatherette-padded cups so even your late game will be comfortable. It's affordable, so there's no pain in the price either.

Pro-gaming optimized, HyperX Cloud is HiFi capable and delivers intense audio with crystal-clear low, mid and high tones plus enhanced bass-reproduction so you can lose yourself while you win. Plus you'll look sharp while playing, thanks to the unique HyperX design.

- > Memory foam ear pads
- > 53mm drivers
- > Interchangeable ear cups



Pro-Gaming Optimized:

- Closed cup design for enhanced passive noise cancellation
- Pure HiFi capable
- Detachable mic
- Solid aluminum build
- Braided cable
- Durable travel pouch

Features/specs on reverse >>



HyperX Cloud Headset

FEATURES/BENEFITS

- > **Comfortable** — memory foam ear cushions with leatherette-padded headband
- > **Customizable** — switch between leatherette and velour ear cushions for varying sound profiles and feel
- > **Compatible** — with PCs, notebooks, tablets, mobile phones, airplane adapters and PS4 consoles
- > **Distinctive** — HyperX branded design in red and black
- > **Guaranteed** — two-year warranty, free technical support

SPECIFICATIONS

Headset:

- > **Transducer type:** dynamic \varnothing 53mm
- > **Operating principle:** closed
- > **Frequency response:** 15Hz–25,000 Hz
- > **Nominal impedance:** 60 Ω per system
- > **Nominal SPL:** 98 \pm 3dB
- > **T.H.D.:** < 2%
- > **Power handling capacity:** 150mW
- > **Sound coupling to the ear:** circumaural
- > **Ambient noise attenuation:** approx. 20 dBa
- > **Headband pressure:** 5N
- > **Weight with microphone and cable:** 350g
- > **Cable length and type:** 1m + 2m extension + 10cm iPhone
- > **Connection:** mini stereo jack plug (3.5 mm)

Microphone:

- > **Transducer type:** condenser (back electret)
- > **Operating principle:** pressure gradient
- > **Polar pattern:** cardioid
- > **Power supply:** AB powering
- > **Supply voltage:** 2V
- > **Current consumption:** max 0.5 mA
- > **Nominal impedance:** \leq 2.2 k Ω
- > **Open circuit voltage:** at f = 1 kHz: 20 mV / Pa
- > **Frequency response:** 100–12,000 Hz
- > **THD:** 2% at f = 1 kHz
- > **Max. SPL:** 105dB SPL (THD \leq 1.0% at 1 KHz)
- > **Microphone output:** -39 \pm 3dB
- > **Length mic boom:** 150mm (include gooseneck)
- > **Capsule diameter:** \varnothing 6*5 mm
- > **Connection:** mini stereo jack plug (3.5mm)



HYPERX PART NUMBER

KHX-H3CL/WR



HyperX is a division of Kingston.

THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2014 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA.

All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-288.US

