





Trying having a look at your power supply through our eyes!

Namely as the heart of your computer! After all, what makes us humans so effective? That's right, a strong heart that reliably provides our body with the right amount of energy at the right time. We developed the STRAIGHT POWER^{E7} series of be quiet! power supply units with that same principle in mind. STRAIGHT POWER^{E7} constantly adjusts the amount of energy it supplies to reflect the current workload facing your computer: from nearly zero watts in stand-by mode to the full bore when working with high-end applications. Up to four separate 12V cables are on hand to provide a stable power supply to all of your system's key components. That helps your entire computer work at the same high levels of efficiency that the STRAIGHT POWER^{E7} achieves!

STRAIGHT POWER^{E7} from be quiet! is available starting immediately, with or without cable management. Both variants boast the 80 PLUS Bronze certificate and are notable quiet running thanks to the be quiet! SilentWings fans. The compatibility with the latest ATX 2.3 technology, multiple PCle slots as well as a high degree of efficiency (up to 88%) prep your PC for top performance. The new, elegant STRAIGHT POWER^{E7} design with a top-quality surface and innovative ventilation grate provides better air circulation and rounds out the product's appearance. That means that STRAIGHT POWER^{E7} is naturally a worthy addition to the accustomed premium quality of the be quiet! family.

Technology that gives its heart and soul.

- Compatible with the latest ATX-version 12V 2.3 / EPS version 2.92
- Active PFC with a PF of 0.99 (at 100% load)
- Quad Rail (4 separated 12V rails)
- Hold-up time of >19ms (at 100% Last)
- Long service life of up to 100,000 hours at 25° Celsius
- Ultra Silent Concept with silent 120mm SilentWings fan from be quiet!

A strong heart, fully committed.

- · All-in-one cable
- Sleeved cable
- Flexible 20/24-Pin mainboard connector
- Multi-GPU compatible through 3x PCIe
- Worldwide mains supply compatibility (100 240Vac)
- Versatile standard connectors (S-ATA, HDD, FDD, P4 for example)
- Multiple connection options. (4+4-Pin for example)
- Full power in 24/7 operation

With this heart vou'll be on the safe side.

Outstanding safety kit:

OCP (Over Current Protection), OVP (Over Voltage Protection), UVP Under Voltage Protection), SCP (Short Circuit Protection), OPP (Over Power Protection), OTP (Over Temperature Protection)

• Internationally proved safety Icons:















A heart for the environment.


- 80 PLUS bronze certification with a high level of energy efficiency of up to 88%
- EuP-ready and low power consumption in stand-by mode of less than 0.5W
- Supports "Energy Star 5.0"* energy standard
- Supports Intel Deep Power-Down C6 status
- 2002/95/EG RoHS and WEEE

In case something's weighing heavy on your heart.

- 3-years manufacturer's warranty
- Rapid help via the be quiet!-hotline:
- +49 (0) 40 736 76 86-98 (from outside Germany) mondays to fridays from 9 a.m. to 5.30 p.m.
- Detailed user manuals in the box and also available as download at www.be-quiet.com



4x 12V rails
1x PCle 6+2-Pin
2x PCle 6-Pin



^{*} The be quiet! STRAIGHT POWER^{L7} power supply has been specially designed to save energy. It fulfils the specifications in Appendix C of the Agreement between the United States government and the European Community (EU) on the coordination of energy-efficient labelling programmes for office equipment of 19/12/2000 (EU Official Journal L 381/26, known as the "Energy Star" Agreement) and is therefore suitable for use with "Energy Star" compliant computers.



All the facts.

Specifications	BQT E7-CM-680W	BQT E7-CM-580W	BQT E7-CM-480W 480		
Continuous power (W)	680	580			
PSU dimensions (cm)	15x8,6x16	15x8,6x16	15x8,6x16		
Hold-up time (ms at 100% load)	>19	>19	>19		
ATX Mainboard connector	20+4-Pin	20+4-Pin	20+4-Pin		
P4 connector	1	1	1		
P8 connector (4+4-Pin)	1	1	1		
PCIe-6+2-Pin GPU connector	2	1	1		
PCIe-6-Pin GPU connector	2	2	1		
IDE 4-Pin connector (HDD, optical disk drives)	7	5	5		
S-ATA 5-Pin connector (HDD, optical disk drives)	7	6	5		
FDD-4-Pin connector (Floppy disk drive)	2	2	2		
Number of fan connectors	2	2	2		
All-in-one cable (S-ATA, IDE, HDD, FDD)	1	1	1		
Number of cables	13	11	10		
Cable lengths to first connector / MB cable in length (cm)	55	55	55		
Maximum cable length (cm)	115	115	115		
EPS version 12V 2.92	•	•	_		

Description	Model- No.	Packaging size (WxHxD in cm)	Box weight (kg)	Quantity per ship. box	Size of ship. box (WxHxD in cm)	Weight of ship. box (kg)	EAN-Code	RRP (€/£)
BQT E7-CM-680W	BN123	25x10x33	3,26	6	28,5x36x66	21	4260052181492	139,90/112,95
BQT E7-CM-580W	BN122	25x10x33	3,15	6	28,5x36x66	20	4260052181478	119,90/96,85
BQT E7-CM-480W	BN121	25x10x33	3,01	6	28,5x36x66	19,2	4260052181454	99,90/80,70

AC Input		100 - 240Vac 50 - 60Hz 9 - 4,5A							
DC Output		3,3V	5V	12V1	12V2	12V3	12V4	-12V	5VSB
DOT				18A	18A	18A	18A		٠
BQT E7-CM-580W 580W	max. current	25A	23A	38A				0,5A	3A
	max. combine	150W		456W				6W	15W
38011	power	580W							