



PRODUCT FEATURES

- THE HAF FEATURES A FULLY-RUGGED APPEARANCE AND IS HOUSED IN A TOUGH CASING TO OFFER OUTSTANDING PROTECTION
- A RUGGED HAF COMES EQUIPPED TO OPERATE WITH UNPARALLELED THERMAL PERFORMANCE
- PATENTED FINGER-PRESS BUTTONS FOR QUICKLY MAINTAINING OR UPGRADING 5.25" DRIVE DEVICES
- REMOVABLE HDD RACKS AND CABLE MANAGEMENT SYSTEM FOR BETTER CABLE ROUTING AND NEATNESS



932 HAF

HIGH AIR FLOW
FULL TOWER CHASSIS



HAF932



HIGH AIR FLOW
FULL TOWER CHASSIS



FRONT VIEW



SIDE VIEW



TOP VIEW

COOLING SYSTEM



EASY ACCESS TO
LIQUID COOLANT
FILL PORT



MESHED BACK SLOT
FOR PROVIDING
PASSIVE COOLING



120MMx2 OR x3
RADIATOR
CAN BE MOUNTED
INSIDE THE TOP
OF THE CASE
(RADIATOR IS OPTIONAL)



THREE 120x25MM
FANS CAN BE MOUNTED
ON THE TOP
FOR EXCELLENT
AIR EXHAUST
(FANS ARE OPTIONAL)



RETAINING HOLES
IN THE REAR
IS PERFECT
FOR
LIQUID COOLING KIT



INDEPENDENT
AIR INTAKE DESIGNED
FOR BOTTOM-MOUNTED
PSU OR INSTALLATION
OF TWO 120MM FANS



HAF932

SPOTLIGHT



LEFT SIDE VIEW



RIGHT SIDE VIEW



RETAINING HOLES
FOR BEST CABLE ROUTING
AND NEATNESS

TOOL-FREE DESIGN



REMOVABLE HDD RACKS
WITH ANTI-VIBRATION PADS
FOR EASY ASSEMBLY
AND REDUCE NOISE



PATENTED BUTTON DESIGN
FOR EASY MAINTENANCE OF
5.25" DRIVE DEVICES



TOOL-FREE CLIPS
FOR ADD-ON CARD
INSTALLATION



RETAINING HOLES
FOR EASY INSTALLATION
OF CPU COOLERS

MISCELLANEOUS



GRID-SHAPE TRANSPARENT
ACRYLIC SIDE WINDOW GIVES
GREAT VIEW OF
THE CASE'S INTERIOR



TOP PLATFORM ALLOWING
USERS TO PLACE PERSONAL
STUFF ON



HAF932

SPECIFICATIONS

AVAILABLE COLOR

BLACK

DIMENSION

(W)230 x (H)545 x (D)575 MM
(W)9.0" x (H)21.5" x (D)22.7"

WEIGHT

13.2 KG / 29.1 lbs

MOTHERBOARD

MICRO - ATX / ATX / E-ATX

5.25" DRIVE BAY

6 (WITHOUT THE USE OF EXPOSED 3.5" DRIVE BAY)

3.5" DRIVE BAY

5 HIDDEN
1 EXPOSED (CONVERTED FROM ONE 5.25" DRIVE BAY)

COOLING SYSTEM

FRONT: 230 X 30 MM RED LED FAN X 1, 700 RPM, 19 dBA
SIDE: 230 X 30 MM STANDARD FAN X 1, 700 RPM, 19 dBA
(SUPPORT 120 X 25 FAN X 4)
TOP: 230 X 30 MM STANDARD FAN X 1, 700 RPM, 19 dBA
(SUPPORT 120 MM FAN X 3 OR 120 MM X 1 + 230 X 30 MM X 1)
REAR: 140 X 25 MM STANDARD FAN X 1, 1200 RPM, 17 dBA
(SUPPORT 120 X 25 MM FAN X 1)

I/O PANEL

USB 2.0 X 4, IEEE1394a X1, eSATA X 1, Mic X 1, Audio X 1

POWER SUPPLY

STANDARD ATX PS2 / EPS 12V (OPTIONAL)



SIDE RED FANS
ARE OPTIONAL