

A case should be...

Meet P4 spec

Harmony

YY-5504/ATX Mid-Tower

YY-3404/Micro ATX Mini-Tower

- For ATX, microATX, Baby AT Motherboard
- Front access top cover, easy for system's maintenance
- Front access USB



YY-3404

YY-5504



The Professional Computer Cases Manufacturer



- Screwless snap-in front panel
- Front access top cover, allows user to assemble and maintain easily in front end; no need to disconnect cables
- Reusable metal cover for all exposed drive bays, allows system re-structure - excellent EMI shielding

Folded metal edge
all around chassis
for safety
assembly

Keep out zonetin
compliant with Intel 2.03
ATX specification,
allows any I/O shield
supplied

Optional 12cm
system fan in rear
side, for air
exhaustion

Screwless fan holder,
allows to hold a
12cm (option)
system fan behind
front panel

Rear lock bracket (option)
reinforces system security

Elastic-slide drive bay
needs only one screw for
drive assembly

Tight chassis and EMI
shielding design for
compliance with CE/FCC
regulation

Built-in M/B standoff, to
save assembly time

*This is the illustration for model YY-54XX middle tower.
Please refer exact spec of each model*

SPECIFICATIONS

YY-3404

Case dimension: 180mm W x 405mm D x 360mm H
7.1" W x 15.9" D x 14.2" H

Motherboard configuration: MicroATX

Drive configuration Up to 5 drive bays : 2 x 5.25" exposed
1 x 3.5" exposed
2 x 3.5" hidden

Optional system cooling fans: 8cm fan for front-mounted and 6cm fan for rear-mounted

Expansion slots and ports: For microATX = 4 slots, 2 DB25 port, 2 DB9 port

Speaker: 2.25" audio speaker

Front panel control: Power switch, Reset switch, Power LED, HDD LED

Materials: Recyclable materials

Flame retardant plastic parts and beze(HB)

Steel chassis

Emissions: Designed to meet FCC class B - 47 CFR part15 / IEC / CISPR 22:1993

Net Weight: 5.5 kg / 12.1 lbs without PSU, 6.5kg / 14.3 lbs with PSU

Color: Cool gray

Power Supply: ATX 200W / 235W / 250W / 300W

UL, CSA, TÜV, CE approved, DoC compliance (A7x 12V/PFC function available)

Options: EMI filter for tail gates, Cooling fan (ball bearing)

Packaging /Shipping: 610pcs / 20' container : 1260pcs / 40' container ; 1348pcs / 40' HQ

YY-5404

Case dimension: 210mm W x 445mm D x 420mm H
8.3" W x 17.5" D x 16.5" H

Motherboard configuration: MicroATX and ATX

Drive configuration Up to 7 drive bays : 3 x 5.25" exposed
1 x 3.5" exposed
3 x 3.5" hidden

Optional system cooling fans: 2 x 12cm fan for front-mounted and rear-mounted

Expansion slots : 7 slots

Speaker: 2.25" audio speaker

Front panel control: Power switch, Reset switch, Power LED, HDD LED

Materials: Recyclable materials

Flame retardant plastic parts and beze(HB)

Steel chassis

Emissions: Designed to meet FCC class B - 47 CFR part15 / IEC / CISPR 22: 1993

Net Weight: 8.0kg / 17.6 lbs without PSU, 9.0kg / 19.8 lbs with PSU

Color: Cool gray

Power Supply: ATX 200W / 235W / 250W / 300W

UL, CSA, TÜV, CE approved, DoC compliance (A7x 12V/PFC function available)

Options: EMI filter for tail gates, Cooling fan (ball bearing)

Packaging /Shipping: 368pcs / 20' container: 768pcs / 40' container ; 912pcs / 40' HQ

*All brand names and trademarks are the property of their respective owners.
*Specifications are subject to change without prior notice.



A case should be...

YEONG YANG TECHNOLOGY Co., Ltd

12F., 778-1, Chung Cheng Road,
Chung-Ho City, Taipei Hsien, Taiwan
Tel: +886-2-32340020 Fax: +886-2-32340014
E-mail: info@yeongyang.com.tw
Web Site: http://www.yeongyang.com

America Branch

YEONG YANG TECHNOLOGY Inc.

18459 E. Railroad St., City of Industry,
CA91748, USA
Tel: +1-626-854-9289 Fax: +1-626-854-1896
E-mail: info@yeongyang.com
Web Site: http://www.yeongyang.com

Eastern office of America Branch

6001 Chapel Hill Road, Suite 104, Raleigh,
NC 27607, USA
Tel: +1-919-859-4004 Fax: +1-919-854-0046
E-mail: info@yeongyang.com
Web site: http://www.yeongyang.com

Europe Branch

YEONG YANG TECHNOLOGY GmbH

Mühlenhagen 130, 20539 Hamburg,
Germany
Tel: +49-40-780461-0 Fax: +49-40-780461-11
E-mail: info@yeongyang.de
Web Site: http://www.yeongyang.de

ZZ16-00054-C