



PRIME
TITANIUM

SPECIAL FEATURES

- ❖ Ultra-High Efficiency, 80 PLUS® Titanium Certified
- ❖ Micro Tolerance Load Regulation
- ❖ Top-Quality 135 mm Fluid Dynamic Bearing Fan
- ❖ Premium Hybrid Fan Control
- ❖ Super lower Ripple Noise (under 20 mV)
- ❖ Extended Hold-up Time (Above 30 ms)
- ❖ Fully Modular Cabling Design
- ❖ Multi-GPU Technologies Supported
- ❖ Gold-Plated High Current Terminals

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
PRIME 850 Titanium	20 A	20 A	70 A	0.3 A	3 A	850 W
	100 W		840 W	3.6 W	15 W	
PRIME 750 Titanium	20 A	20 A	62 A	0.3 A	3 A	750 W
	100 W		744 W	3.6 W	15 W	
PRIME 650 Titanium	20 A	20 A	54 A	0.3 A	3 A	650 W
	100 W		648 W	3.6 W	15 W	



WIRE CONFIGURATION

Cable						
Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 650 mm	PCI-E (8P / 6P)	SATA	Peripheral (4P)	FDD (4P)
PRIME 850 Titanium	1	2	6	10	5	1
PRIME 750 Titanium	1	2	4	10	5	1
PRIME 650 Titanium	1	2	4	6	5	1



Safety & EMI / EMC



Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: L 170 x W 150 x H 86 mm



Specifications may change without prior notice



Headquarters Tel: +886-2-2659-0338 | Fax: +886-2-2659-0530 | sales@seasonic.com | www.seasonic.com

USA Tel: +1 626-969-9966 | Fax: +1 626-969-9986 | ssa.sales@seasonic.com

Europe sse.sales@seasonic.com

Japan Tel: +81-3-6805-4085 | ssj.sales@seasonic.com